







Swiveling hose tails

The swiveling hose tails in Stainless Steel can be used for a swiveling connection between a flexible hose and a spray gun for more comfort in use and longer life of the hoses. Hose tails available in 10mm, 13mm, 16mm and 19mm. The swiveling hose tails are for the low pressure environment and can take up to 40 bar. (brass up to 10 bar)

Brass	Product Code	Description
	SWIFM1/2	Brass swiveling hose tail 13mm, 1/2" male thread. Full Bore 10 mm
Stainless Steel		
	SWIFB10	Stainless Steel swiveling hose tail 10mm x 1/2" male thread. Full Bore 6 mm
	SWIFB13-C17	Stainless Steel swiveling hose tail 13mm x 1/2" male thread and 17mm collar. Full Bore 10 mm
	SWIFB13-C20	Stainless Steel swiveling hose tail 13mm x 1/2" male thread and 20mm collar. Full Bore 10 mm
	SWIFB16-C21	Stainless Steel swiveling hose tail 16mm x 1/2" male thread and 21mm collar. Full Bore 13 mm
	SWIFB19-C24	Stainless Steel swiveling hose tail 19mm x 1/2" male thread and 24mm collar. Full Bore 14 mm

The hose protection spring



Check pictures below to see the advantages of using a hose protection spring.



Hose with normal hose tail



Hose tail with protection

Swiveling hose tails with flexible springs		
	SWIFB13-C20-SP	Stainless Steel swiveling hose tail 13mm x 1/2" male thread and 20mm collar; with welded inside hose protection spring(20cm).
	SWIFB16-C21-SP	Stainless Steel swiveling hose tail 16mm x 1/2" male thread and 21mm collar; with welded inside hose protection spring(20cm).
	SWIFB19-C24-SP	Stainless Steel swiveling hose tail 19mm x 1/2" male thread and 24mm collar; with welded inside hose protection spring(20cm).
Tail with swiveling hex nut flat or conical sealing		
	RVSW013-C20-F-SP	Stainless Steel hose tail 13mm; 1/2" female screw cap with flat sealing; welded inside hose protection spring.
	RVSW013-C20-C-SP	Stainless Steel hose tail 13mm; 1/2" female screw cap with conical sealing; welded inside hose protection spring.
	RVSW016-C21-C-SP	Stainless Steel hose tail 16mm; 1/2" female screw cap with conical sealing; welded inside hose protection spring.

[All other dimensions or shapes are available on demand](#)
[Also available different hose tails with protection springs.](#)